



AccessMount™

Tablet Surface Mount
Adjustable and Secure Mount



workFLO™

Adjustable Height
Non-powered Workstation
(with tablet mount)



workFLO™

Single Monitor/All-In-One
Non-powered Workstation



AccessPoint™

Single Monitor
Powered Workstation



AccessPoint™

Dual Monitor
Powered Workstation

Supporting Your Expanding Telehealth Applications.

With a wide range of customizable mobile and mounted solutions,
we can tailor a solution to meet your specific telehealth delivery needs.

Supports a wide variety of telehealth accessories and technology solutions.



AccessPoint™ Single Monitor Powered Workstation

- Supports larger monitor formats with dual monitor options available
- One-way and two-way video conferencing technology
- High resolution cameras to review patient condition
- Wireless LAN bridge to enable wireless connectivity



AccessPoint™ Dual Monitor Powered Workstation

- Enables remote delivery of specialized care and timely diagnostics
- Monitor arms simultaneously fold inward with one hand to easily fit through doors or tight spaces
- Monitor configuration provides separate viewing access for caregiver and patient
- Mount a video or web camera above the monitor, facing forward; camera travels with the monitor through its entire range of motion
- Front storage options are perfect for critical diagnostic equipment

Work Surface Height (Adjustable Range)	Weight Capacity	Work Surface Area	Workstation Foot Print	Construction	Casters
914MM - 1219mm (36IN - 48IN)	Single Monitor 11kgs (25lbs)	1723cm ² (267in ²)	425mm x 445mm (16.75in x 17.5in)	<ul style="list-style-type: none"> • Powder-coated, cast aluminum with Microban® infused antimicrobial protection. • Anodized extruded aluminum column. • Polymer work surface and touch points with Microban® infused antimicrobial protection. 	Four, single wheel 5" casters: 3 braking, 1 directional/tracking
	Dual Monitor 13kgs (30lbs) 15lbs per side max				

Power Options:

- Li-Nano (Lithium-Iron Nanophosphate) battery options or LiFe (Lithium-Iron Phosphate)
- Can be configured to be powered by direct current (DC), alternating current (AC), or a combination of the two.
- Our DC optimized power with selectable voltage delivers 20% greater efficiency (runtime) than AC powered carts available in the market
- Also available as a non-powered cart



Contact your TouchPoint Medical representative to learn more about these options and to discuss additional accessories specific to your point-of-care application. Visit touchpointmed.com/contact to get in touch with your local representative.



workFLO™ Single Monitor/All-In-One Non-powered Workstation

- Antimicrobial work surface on all composite and powder coated materials.
- Lift Mechanism: Gas spring push button actuation.
- Tech Bay: Key lock computer security with universal key. Optional key codes available.

Height Adjustable Range	Weight Capacity	Cart Weight	Cart Foot Print	Main Material	Casters	Mounting Options
898-1198MM (35-47IN)	10kgs (22lbs)	29.9kgs (66lbs)	538mm x 574mm (21.19in x 22.58in)	Aluminum alloy/ Stainless steel/ ABS(VO)	127mm (5in), 3 locking, 1 directional/tracking caster for ease of mobility	Single Monitor, Secure (no drift) positioning with Tilt/Swivel VESA 75/100 mount, or Tablet mount.

Part Number: WF-CSX-AH



workFLO™ Adjustable Height Non-powered Workstation*

- Antimicrobial work surface on all composite and powder coated materials.
- Lift Mechanism: Gas spring push button actuation.

Height Adjustable Range	Weight Capacity	Cart Weight	Cart Foot Print	Main Material	Casters	Mounting Options
800-1050MM (31.5-41.5IN)	8kgs (17.6lbs)	12.7kgs (28lbs)	Ø604.5mm (Ø23.8in) maximum	Aluminum alloy/ Stainless steel/ ABS(VO)	62.5mm (2.5in), 5 locking	Laptop with power adapter containment basket, standard; optional laptop security bracket and tablet mount.

Part Number: WF-RLX-AH

*With Tablet Surface Mount (AM-TABMNT-S). Compatible with VESA Mount (WF-VESA-MNT-LT). Also available as a fixed height workstation (WF-RLX-FH).



AccessMount™ Tablet Surface Mount

- Used for cart or desk applications.
- Can hold up to a 12.9in tablet (7-11mm thickness, 126-220mm wide).
- Mounting is easy-to-use, quick adjustment with self-contained tool.
- Three point articulation.
- Concealed cable management.

Length	Tablet Width	Tablet Thickness	Load Rating	Mounting Surface Thickness
225mm (8.9in)	146-200mm (5.75in - 8.66in)	7-11mm (.276in - .433in)	0.75kgs (1.58lbs)	up to 40mm (1.58in)

Part Number: AM-TABMNT-S

KEY BENEFITS



Variety of Configurations



Lightweight Design



Ergonomic Design Elements



Concealed Cable Management



Easy Cleaning



Antimicrobial Infused Cart Material



Reliable Positioning Technology



Easy Height Adjustment



Ready to deploy to your team upon arrival



Field Upgradeable Options

touchpointmed.com

1.800.947.3901

info@touchpointmed.com

20200601-BR-TPM Telehealth Offering-EN.indd

BRINGING CARE FORWARD.™